



## UNIVERSAL HEATING CABLE SCU SERIES



UNCOUPLING MEMBRANES OR  
CABLE SPACERS INSTALLATION

COMPATIBLE WITH MOST  
TYPES OF FLOORING

OPTIMAL AND UNIFORM HEAT

FLEXIBLE,  
EASY-TO-HANDLE CABLE

### TECHNICAL SPECIFICATIONS:

Voltages available: 120 V, 240 V/208 V  
Surface (membranes): from 12.9 to 289.0 ft<sup>2</sup>  
Surface (cable spacers): from 12.5 to 368.7 ft<sup>2</sup>  
according to space and density available

### POWER:

9 W/ft<sup>2</sup> - 4 spaces (cable spacers)  
12 W/ft<sup>2</sup>- 3 spaces (membranes or cable spacers)



UNCOUPLING  
MEMBRANE AVAILABLE  
TO EASE INSTALLATION OF  
CERAMIC FLOOR



## HEATING CABLE MAT SFM/SFMC SERIES



NEW!  
CUSTOM SIZES  
NOW AVAILABLE

PERSIA™  
CUSTOM

QUICK, SAFE AND EASY INSTALLATION

STANDARD AND CUSTOM SIZES AVAILABLE

THE MEMBRANE PROTECTS THE CABLE DURING  
INSTALLATION.

COMPATIBLE WITH ALL TYPES OF MORTAR, ADHESIVE  
MORTAR, POLYMER-MODIFIED MORTAR (THINSET)  
AND SELF-LEVELLING MORTAR TYPICALLY USED  
FOR FLOOR COVERINGS

### TECHNICAL SPECIFICATIONS:

Voltages available: 120 V, 240 V/208 V  
Surface: from 12.3 to 144.0 ft<sup>2</sup>

### POWER:

9 W/ft<sup>2</sup> @ 208 V  
12 W/ft<sup>2</sup> @ 120 V or 240 V



## HEATING CABLE ON LATTICE FOR CONCRETE SECM SERIES



IDEAL FOR NEW CONSTRUCTION, RESIDENTIAL  
AND COMMERCIAL PROJECTS

CONCRETE SLAB HEATING WITH NO LIQUID OR PUMP

CAN BE INSTALLED WITH OR WITHOUT  
A METAL FRAME FOR REINFORCED CONCRETE

PERFECT FOR PEOPLE WITH ALLERGIES

### TECHNICAL SPECIFICATIONS:

Voltages available: 240 V/208 V  
Surface: from 12 to 292 ft<sup>2</sup>

### POWER:

9 W/ft<sup>2</sup> @ 208 V  
12 W/ft<sup>2</sup> @ 240 V



## SNOW MELTING SYSTEM SSC/SSCM SERIES



NEW!

AVAILABLE IN MAT OR CABLE FORMAT

LONGER INFRASTRUCTURE LIFESPAN

REDUCES THE NEED FOR CHIMICALS  
AND ABRASIVES

CAN BE INSTALLED UNDER CONCRETE,  
ASPHALT AND PAVERS

### TECHNICAL SPECIFICATIONS:

Voltages available: 240 V/208 V, 347 V  
Surface: from 9 to 120 ft<sup>2</sup>

### POWER:

50 W/ft<sup>2</sup> @ 240 V or 347 V (3 in. spacing)  
37.5 W/ft<sup>2</sup> @ 208 V (3 in. spacing)





## 360 COMFORT

°STELPRO is a family-owned business established in Quebec for over 35 years, renowned in the electric heating industry, heating cables, ventilation (HVAC) and electronic controls. North American leader in its market, °STELPRO offers quality heating products designed and manufactured in Canada.

°STELPRO is your global comfort solution to enhance your clients' living environment. Peak performance is complemented by optimal efficiency and striking designs, uniting all aspects of 360 comfort.



**STELPRO.COM**  
1 844-STELPRO



DEP\_CABLESCHAUFFANTS\_EN\_0719

### CONSTANT WATTAGE



#### PIPE FREEZE PROTECTION HEATING CABLE SCPT SERIES

PREVENTS PIPE BREAKAGE AND WATER DAMAGE

IDEAL FOR PLASTIC OR METAL PIPES

LIGHTED PLUG POWER INDICATOR

INTEGRATED THERMOSTAT THAT TRIGGERS AT 3 °C (37 °F) TO PREVENT FREEZING

**POWER:**  
7 W/ft @ 120 V



#### ROOF AND GUTTER DE-ICING HEATING CABLE SCRG SERIES

PREVENTS ROOF DAMAGE AND LEAKING

KEEPS GUTTERS AND DOWNSPOUTS FLOWING

PREASSEMBLED • READY TO INSTALL

THERMOSTAT WITH TEMPERATURE AND MOISTURE SENSORS (OPTIONAL)

**POWER:**  
5 W/ft @ 120 V



### SELF-REGULATING



#### FREEZE PROTECTION CABLE REEL SSFR SERIES

ENERGY EFFICIENT

EASY INSTALLATION

SAFE

POWER CONNECTION, SPLICE, TEE AND END SEAL KIT

**POWER:**  
5 W/ft and 8 W/ft @ 120 V  
5 W/ft, 8 W/ft and 10 W/ft @ 240 V



#### FREEZE PROTECTION PREASSEMBLED CABLE SSFP SERIES

SELF-REGULATING PREASSEMBLED CABLE

FOR RESIDENTIAL AND COMMERCIAL APPLICATIONS

240 V MODELS AVAILABLE WITH THREE-WIRE PIGTAIL

WIDE VARIETY OF LENGTHS

**POWER:**  
5 W/ft at 50°F (10°C) @ 120 V and 240 V



### THE ULTIMATE COMFORT

HEATING CABLE SOLUTIONS

